



Goodrich Global
SINCE 1983

GEFF SPC

Item	Standard Reference	Main Parameter
Name		CLICK SPC 4.0/0.55mm + 1.0mm IXPE
Size	EN ISO 24342	Deviation $\leq 0.15\%$ of nominal length up to mm maximum
Overall thickness	EN ISO 24346	4.0mm + 1.0mm IXPE
Wear layer thickness	EN ISO 24340	0.55mm
Total mass per unit area	EN ISO 23997	13%/-10%
Squareness and straightness	EN ISO 24342	Pass
Dimensional stability after exposure to	EN ISO 23999	$\leq 0.25\%$
Curling after exposure to heat	EN ISO 23999	$\leq 2\text{mm}$
Usage classification	EN ISO 10874	23,33,42
Abrasion resistance	EN 660-2	Group T
Slip resistance	EN 13893	DS
	DIN 51130	R10
Color fastness to artificial light	EN ISO 105 B02	≥ 6
Flexibility	EN ISO 24344	20mm
Effect of castor chair	ISO 4918	Pass
Impact sound reduction	ASTM E 492-09	IIC=58
Chemical resistance	EN ISO 26987	GOOD
Toxicity	EN71	Non-toxic
Resistance to staining	EN ISO 26987	GOOD
Heavy metals	Rohs	ND
Phthalate	EN 14372	ND
Formaldehyde emission	EN 717-1	E1
Fire classification	EN 13501-1	Bf1-s1
Underfloor heating		Not more than 28°C
Antibacterial	JISZ2801	Pass
SVHC	REACH	Pass
	DIBT/AgBB	Pass
VOC	French VOC Regulation	A+
	California Specification 01350	Pass

