

PULSE



SPECIFICATIONS

COLLECTION NAME	: PULSE SQ
YARN	: 100% nexlon™ Nylon
CONSTRUCTION	: Tufted Multi-Level Loop
DYE METHOD	: Solution Dyed
GAUGE	: 1/12"
STITCHES PER INCH	: 11.2 per inch
PILE HEIGHT	: 3.50mm to 4.50mm (+/-0.5mm)
TOTAL HEIGHT	: 7.7mm (+/-0.5mm)
PILE WEIGHT	: 16 oz/sy (550gm/sm)
TOTAL WEIGHT	: 146 oz/sy (4950gm/sm)
PRIMARY BACKING	: Non-woven
SECONDARY BACKING	: Recyclable TUNTEX Commercial Duraback
SIZE	: 50 x 50 cm/tile
PACKING	: 20 pcs (5 sm)/box
STAIN TREATMENT	: Stainshield™ Soil & Stain Treatment


* As with all dyed products, colours are subject to dye lot variations.

PERFORMANCE SPECIFICATIONS

COLOURFASTNESS	: Grade ≥ 4 (AATCC 16)
FLAMMABILITY	: Class 1 (ASTM E648)
SMOKE DENSITY	: Passed (ASTM E662)
STATIC PROPENSITY	: ≤ 3.0 kV (AATCC-134)
CRI GREEN LABEL PLUS	: GLP7116
SGBC	: Leader
WARRANTY	: 15 Years



T10503 FAWN



T10512 FIRE



T10505 CLAY



T10513 SHAMROCK




T10507 PEWTER



T10514 SAPPHIRE

RECOMMENDED INSTALLATION METHODS :



Brick



Ashlar

